

Category 6 High Density Patch Panel, Unloaded – 0.5U



This 24 Port 0.5U High Density Patch Panel delivers a high density offering with the benefit of a single row of keystone outlets. The single row of outlets means that the installation is straight forward and allows an individual outlet to be removed if required. As the panel is only 0.5U in height it allows, by using two panels together, the ability to present 48 keystone outlets in 1U of rack space. Using two 0.5U panels ensures that the outlets are all aligned the correct way up. The Jack to be ordered separately

Features

- High density placement, 24 ports in 0.5U
- Supplied with cable management bar
- Ideal for standard and pre-terminated installations
- Terminating 4 pairs, 22-26 AWG wires
- Universal labels color-coded for T568A and T568B wiring scheme
- Covered under 3C3® Product Warranty

Mechanical Specifications

Panel	:	Metal SPCC
Panel Thickness	:	1.5mm
Panel Color	:	Black
Port Count	:	24Nos
Each port Numbering	:	Yes
Outlet Type	:	Unshielded
Width	:	19" (482.5mm)
Height	:	0.5U(22mm)
Depth	:	96mm

Category 6 High Density Patch Panel, Unloaded – 0.5U

Environmental Specifications

Operating Temperature	:	-40°C to +70°C
Storage Temperature	:	-40°C to +70°C
Humidity	:	10% - 90% RH

Standard Compliances/Certifications

- RoHS Certified
- ASTM B 117 Certified

Ordering Information

Product Code	Description
16800	Copper Panel Unshielded C6, 24Port Unloaded 0.5U, wire manager included