

# Category 6 UTP Keystone Jack



The UTP RJ45 Keystone Outlet conform to Category 6 class E performance. Each jack is available with a 180° termination design, wiring diagram and conductor protection cap. The jacks are available in various colors for ease of service identification.

## Features

- Complies to ANSI/TIA 568.D-2, IEC/ISO 11801 & IEC60603-7-41
- Integrate with T568A and T568B wiring Diagram.
- Fast Termination with One Punch Keystone Tool.
- ETL Verified & UL Listed
- Covered under 3C3® Performance Warrant

## Mechanical Specifications

Contact Material	:	Gold Plated with Nickel Undercoat
Plastic Housing	:	ABS UL94V-0
Plug Insertion Life (RJ45 Contacts)	:	≥ 750 Cycles
Plug and Outlet Contact force	:	≥ 100 Grams
Plug Retention Force	:	≥ 11lbf
Durability (IDC Life)	:	200 termination cycles
Wiring Pattern at rear end	:	T568A & T568B
PCB Material & Thickness	:	FR-4, 1.2mm thickness
Outlet wire material and thickness	:	0.35mm Phosphor bronze gold over nickel plating
IDC Conductor	:	0.5mm Phosphor bronze, Tin-plating
Contact Compatibility	:	Accommodate 23 to 26AWG solid
Design	:	180°

## Electrical Specifications

Insulation Resistance	:	≥ 500MΩ
Contact Resistance	:	≤ 20mΩ
Current rating	:	1.5 Amps
DC Resistance	:	≤ 0.3Ω
DC/AC Volt Endurance	:	DC1000V/AC750V 1min

# Category 6 UTP Keystone Jack

## Environmental Specifications

Operating Temperature	:	-10°C to + 60°C
Storage Temperature	:	-40°C to + 70°C
Operating Humidity	:	10% to 90% PH

## Standard Compliances/Certifications

- ETL Verified 4-connector channel to ANSI/TIA-568.2-E and ISO/IEC 11801-1
- UL Verified
- RoHS Certified

## Ordering Information

Product Code	Description
12200	Keystone Unshielded Jack, 180°, C6, Blue
12201**	Keystone Unshielded Jack 180°, C6, Green
12202	Keystone Unshielded Jack, 180°, C6, Red
12203	Keystone Unshielded Jack, 180°, C6, Yellow
12204**	Keystone Unshielded Jack, 180°, C6, White
12205	Keystone Unshielded Jack, 180°, C6, Grey
12206	Keystone Unshielded Jack 180°, C6, Black
12208**	Keystone Unshielded Jack, 180°, C6, Orange

\*\* *MOQ is Applicable*