

Category 6 UTP Lockable Patch Cord



High Speed Gigabit Lockable UTP Patch Cable, LSZH, C6 are manufactured using high quality unshielded four pair Category 6 Stranded cable. It is highly recommended for Datacenter and where physical security is a prime importance. Auto lock the jack by inserting the lockable patch cord and to unlock you should use the key.

Features

- Complies to ANSI/TIA-568.2-D Standard & ISO/IEC 11801
- Quality 24AWG Stranded Flexible Cable
- High grade 50µm Gold Plated RJ45 connectors
- Customized lengths
- Single end/both end lockable solution
- Compatible with special faceplate
- Built with patented design for enhanced performance (Patent No. 518987)
- Covered under 3C3® Performance Warranty

Mechanical Specifications

Conductor AWG	: 24
Conductor Material	: Stranded Bare Copper
Type of Cable	: UTP
Number of Pairs	: 4
Application	: Indoor
Insulation Diameter	: 1.05±0.05mm
Insulation Material	: PE
Insulation Thickness	: 0.155mm
Jacket Type	: LSZH
Jacket color	: Grey
Cable Diameter	: 5.99±0.3mm

Category 6 UTP Lockable Patch Cord

Electrical Specifications

Conductor DC Resistance	:	14Ω/ 100m
Resistance Unbalance	:	50mΩ
Impedance	:	100 ± 15%
Frequency	:	250MHz

Environmental Specifications

Installation Temperature	:	0°C to 50°C
Storage Temperature	:	-20°C to +70°C
Operating Temperature	:	-10°C to +60°C

Standard Compliance/Certifications

- RoHS Certified

Ordering Information

Product Code	Description
272D0-XXXX	High Speed Gigabit 24AWG UTP Lockable Patch Cord, LSZH, C6 D = Color (0 – Blue, 1 – Green**, 2 – Red**, 3 – Yellow**, 4 – White**, 5 – Grey, 6 – Black**) XXXX = length in Decimeter
15290	Key for Lockable Patch Cord