


Category 6A S/FTP Solid Patch Cords, LSZH



Cat6A S/FTP Patch cords are manufactured using high quality shielded 4 Pair Solid Bare Electrolytic Grade Copper. These high-performance components are available in broad range of lengths. They are designed to meet or exceed Cat6A specifications. Conductors are securely mated with shielded RJ45 plug and designed to deliver superior performance.

Features

- Cable Conformance ANSI-TIA 568.2-D, ISO/IEC 11801 & IEC 61156-6 Standard
- Quality 23 AWG Solid Cable
- High Grade 50micron Gold Plated Fully Shielded RJ45 connectors
- Transparent Strain Relief Boot with Soft Latch-cover design
- Covered by the 3C3® Performance Warranty

Mechanical Specifications

Conductor AWG	: 23
Conductor Material	: Solid Bare Copper
Type of Cable	: S/FTP
Braid Shield	: Tinned Copper Braiding
Individual Pair Shield	: Aluminum/PET Tape
Number of Pairs	: 4
Insulation Material	: Foamed Polyethylene
Jacket Type	: LSZH
Cable Diameter	: 7.5mm Nominal
Jacket color	: Grey

Category 6A S/FTP Solid Patch Cords, LSZH

Electrical Specifications - Cable

Conductor DC Resistance	:	≤9.38Ω/100m
Resistance Unbalance	:	5% Max
Mutual Capacitance	:	5.6nF/100 meters Max
Impedance	:	100 ± 15%
Capacitance Unbalance	:	
Pair/Ground	:	330PF/100Mtrs. Max.

Environmental Specifications

Installation Temperature	:	0°C to 50°C
Storage Temperature	:	-20°C to +70°C
Operating Temperature	:	-20°C to +60°C

Standard Compliances/Certifications

- RoHS Certified

Ordering Information

Product Code

3B350-XXXX

Description

High Speed 10Gigabit 23AWG S/FTP Solid Patch Cord, Grey, LSZH, C6A

B= Type (3 - Straight, 4 - Cross)

XXXX = Length in Decimeter (0100 -1Mtr ~ 9900 - 99Mtr)