

## Category 6A U-FTP Cable - LSZH



High Speed 10Gigabit Ethernet U-FTP 500 MHz Class EA / Category 6A cable Consists of HDPE Insulated 8 X 23AWG Solid Bare Electrolytic Grade Copper Conductors Twisted as 4 Pairs, Aluminum / Polyester Tape shielding and LSZH Outer Jacket. It supports 10/100/1000Base-T, 155Mbps ATM, IEEE 802.3an (10GBase-T) Standard.

#### **Features**

- Complies to ANSI/TIA-568.2-D Category 6A & ISO/IEC 11801 Class EA
- Fire Rating as per IEC 60332-1
- Full Power Sum Performance
- Supports 10Gigabit Ethernet to a full 100m up to 500 MHz
- Excellent Shielding prevents Alien Crosstalk
- Covered under 3C3<sup>®</sup> Performance Warranty

#### **Mechanical Specifications**

Conductor AWG : 23

Conductor Material : Solid bare Copper

Conductor Count : 8

Insulation Material : Skin-Foam-Skin Polyethylene

No. of pair : 4

Color Code

Pair #1 : Blue, White and Blue
Pair #2 : Orange, White and Orange
Pair #3 : Green, White and Green
Pair #4 : Brown, White and Brown
Individual Pair : Aluminum -Polyester Tape

Drain Wire : ATC
Outer Sheath : LSZH
Outer Sheath Color : Grey

Outer Sheath Thickness :  $0.55 \pm 0.05$ mm Overall cable diameter :  $7.4 \pm 0.3$  mm

RIP Cord : No Cross filler : HDPE

Page 1 of 2

Kindly note that any specifications including design, measurements, size, dimension, weight and material specifications mentioned across any technical or commercial document are change by 3C3 India Pvt. Ltd., without any notice.

Document Version: 10350/V3 Date of Revision: 08/2025 Log On to www.3c3.com for recent updates.



# Category 6A U-FTP Cable - LSZH

## **Electrical Specifications**

Delay Skew : <45ns NVP : 69%

Bending radius : Minimum 8 x cable diameter

Pulling force : 11.5kg
Maximum propagation delay : 536ns/100m

@500MHz

Frequency	Max. IL	Min.	Min	Min	Min	Min	Min	Min RL
	(dB)	NEXT	<b>PSNEXT</b>	ACRF	<b>PSACRF</b>	<b>PSANEXT</b>	<b>PSAACRF</b>	(dB)
	, ,	(dB)	(dB)	(dB)	(dB)	(dB)	(dB)	, ,
500MHz	≤49.3	≥ 33.8	≥31.8	≥13.8	≥10.8	≥52	≥24.2	≥ 15.2

#### **Environmental Specifications**

Installation Temperature : 0°C to 50°C
Storage Temperature : -20°C to +70°C
Operating Temperature : -10°C to +60°C

### **Flame Properties**

Flammability Test : IEC 60332-1
Acid Gas Emission Test : IEC 60754-1 & 2
Smoke Density Test : IEC 61034-2

## **Standard Compliance/Certifications**

RoHS Certified

#### **Ordering Information**

Document Version: 10350/V3

Product Code Description

High Speed 10G Ethernet U-FTP 500 MHz Class EA LSZH Cable,

C6A

Page 2 of 2

Kindly note that any specifications including design, measurements, size, dimension, weight and material specifications mentioned across any technical or commercial document are change by 3C3 India Pvt. Ltd., without any notice.

Date of Revision: 08/2025

Phone: 1800-2020198 | Email: sales@3c3.com | www.3c3.com

Log On to www.3c3.com for recent updates.