


## Category 6A U/UTP Solid Patch Cords, LSZH



Cat6A U/UTP Patch cords are manufactured using high quality 4 Pair Solid Bare Electrolytic Grade Copper. These high-performance components are available in broad range of lengths. They are designed to meet or exceed Cat6A specifications. Conductors are securely mated with unshielded RJ45 plugs and designed to deliver superior performance.

### Features

- Cable Conformance ANSI-TIA 568.2-D, ISO/IEC 11801 & IEC 61156-6 Standard
- Quality 23 AWG Solid Cable
- High Grade 50micron Gold Plated Unshielded RJ45 connectors
- Transparent Strain Relief Boot with Soft Latch-cover design
- Covered by the 3C3® Performance Warranty

### Mechanical Specifications

Conductor AWG	:	23
Conductor Material	:	Solid Bare Copper
Type of Cable	:	U/UTP
Number of Pairs	:	4
Insulation Material	:	High Density Polyethylene
Jacket Type	:	LSZH
Cable Diameter	:	7.20±0.30mm Nominal
Jacket color	:	Blue, Green, Red, Yellow, White, Grey, Black, Orange, Purple

### Electrical Specifications - Cable

Conductor DC Resistance	:	≤9.38Ω/100m
Resistance Unbalance	:	5% Max
Mutual Capacitance	:	5.6nF/100 meters Max
Impedance	:	100 ± 15%
Capacitance Unbalance	:	330PF/100 mtrs. Max.
Pair/Ground	:	

# Category 6A U/UTP Solid Patch Cords, LSZH

## Environmental Specifications

Installation Temperature	:	0°C to 50°C
Storage Temperature	:	-20°C to +75°C
Operating Temperature	:	-20°C to +70°C

## Standard Compliances/Certifications

- RoHS Certified

## Ordering Information

**Product Code**  
3B3D0-XXXX

### Description

High Speed 10Gigabit 23AWG U/UTP Solid Patch Cord, LSZH, C6A

B= Type (0 - Straight, 1 - Cross)

D = Colors (0 – Blue\*\*, 1 – Green\*\*, 2 – Red\*\*, 3 – Yellow\*\*, 4 – White\*\*, 5 – Grey, 6 – Black, 7 – Orange\*\*, 8 – Purple\*\*)

XXXX = Length in Decimeter (0100 -1Mtr ~ 9900 - 99Mtr)

\*\* MOQ is applicable