

Category 6A Unshielded Patch Panel, Loaded -1U



The rack mountable Patch Panel offers fast and reliable installation of Unshielded cables on to a jack. A rear cable management bar is supplied which acts as stress reliever for terminated cables. Each port of the panel is numbered for clear port identification. Patch Panel includes mini cable ties, cage nuts and rare cable management

Features

- 19" RJ-45 Patch Panel with 24 ports on 1U
- Strain relief and cable management with inbuilt wire manager
- Universal wiring T568 A or B wiring pattern
- Snap in type
- UL Listed
- Covered under 3C3® Product Warranty

Mechanical Specifications

Panel : Metal SPCC
Panel Thickness : 1.5mm
Panel Color : Black
Each port Numbering : Yes

Jack Type : Unshielded

Jack Contact Material : Gold Plated Bronze pins

Plastic Housing : PCUL94 V2 Plug Insertion Life : \geq 750 Cycles

(RJ 45 Contacts)

Plug and Jack Contact Force : ≥ 100 Grams with FCC Compliant RJ-45 Plug

Plug Retention Force : ≥ 15Nm

Durability (IDC Life) : 200 termination cycles

Electrical Specifications

 Insulation Resistance
 : ≥ 500mΩ

 Contact Resistance
 : ≤10mΩ

 Current rating
 : 1.5 Amps

 DC Resistance
 : ≤ 0.1Ω

DC/AC Volt Endurance : DC1000V/AC750V 1min

Wiring Pattern at rear end : T568A & T568B

Page 1 of 2

Kindly note that any specifications including design, measurements, size, dimension, weight and material specifications mentioned across any technical or commercial document are change by 3C3 India Pvt. Ltd., without any notice.

Document Version: 11300/V3 Date of Revision: 08/2025 Log On to www.3c3.com for recent updates.

Phone: 1800-2020198 | Email: sales@3c3.com | www.3c3.com



Category 6A Unshielded Patch Panel, Loaded -1U

Environmental Specifications

Operating Temperature : $-10^{\circ}\text{C to} + 60^{\circ}\text{C}$ Storage Temperature : $-40^{\circ}\text{C to} + 70^{\circ}\text{C}$ Humidity : $10^{\circ} - 90^{\circ}\text{RH}$

Standard Compliance/Certifications

- RoHS Certified
- ASTM B 117 Certified
- UL Listed

Ordering Information

Product Code

11300

Description

Copper Panel Unshielded C6A, 24 Port Loaded 1U wire manager included

Page 2 of 2

Kindly note that any specifications including design, measurements, size, dimension, weight and material specifications mentioned across any technical or commercial document are change by 3C3 India Pvt. Ltd., without any notice.

Document Version: 11300/V3 Date of Revision: 08/2025 Log On to www.3c3.com for recent updates.

Phone: 1800-2020198 | Email: sales@3c3.com | www.3c3.com