

Copper High Density Patch Panel, 48Port Unloaded – 1U



High Density Snap-In Patch Panel offers fast and reliable installation of un-shielded cables; A rear cable Management bar is supplied which acts as stress reliever of terminated cables. Each port of the panel is numbered and as a designated label id area for clear port identification. Patch Panel comes with mini cable ties, cage nuts and rare cable management as a standard.

Features

- High density placement, 48 ports in 1U
- Supplied with cable management bar
- Ideal for standard and pre-terminated installations
- Terminating 4 pairs, 22-26 AWG wires
- Universal labels color-coded for T568A and T568B wiring scheme
- Covered under 3C3® Product Warranty

Mechanical Specifications

Panel	:	Metal SPCC
Panel Thickness	:	1.5mm
Panel Color	:	Black
Port Count	:	48 Nos
Outlet Type	:	Unshielded
Each port Numbering	:	Yes
Height	:	1U

Environmental Specifications

Operating Temperature	:	-40°C to +70°C
Storage Temperature	:	-40°C to +70°C
Humidity	:	10% - 90% RH

Ordering Information

Product Code	Description
16801	High Density Copper Panel Unshielded, 48Port Unloaded 1U wire manager included

Page 1 of 1

Kindly note that any specifications including design, measurements, size, dimension, weight and material specifications mentioned across any technical or commercial document are change by 3C3 India Pvt. Ltd., without any notice.