

Copper V-Shaped Angled Patch Panel Shielded Loaded – 1U



Patch Panel V-shaped Angled, 1U offers fast and reliable installation of shielded cables, a rear cable management bar is supplied which acts as stress reliever of terminated cables. Each port of the panel is numbered and has designated label area for clear port identification.

Features

- 19" RJ-45 Patch Panel with 24 ports on 1U
- Strain relief and cable management
- Grounding Bolt included
- Accommodates Shielded Keystone Jack
- RoHS Compliant & UL Listed
- Covered under 3C3® Product Warranty

Mechanical Specifications

Panel	:	Metal SPCC
Panel Thickness	:	1.2mm
Panel Color	:	Black
Each port Numbering	:	Yes
Grounding	:	Yes
Port Count	:	24
Compatible Jack Type	:	Shielded
Jack Contact Material	:	Phosphor Bronze, Tin (8Pins- Gold Plating)
Inner Plastic Housing	:	PCUL94 V2
Plug Insertion Life (RJ 45 Contacts)	:	≥ 750 Cycles
Plug and Jack Contact Force	:	≥ 100 Grams with FCC Compliant RJ-45 Plug
Plug Retention Force	:	≥ 15Nm
Durability (IDC Life)	:	200 termination cycles

Electrical Specifications

Insulation Resistance	:	≥ 500mΩ
Contact Resistance	:	≤10mΩ
Current rating	:	1.5 Amps
DC Resistance	:	≤ 0.1Ω
DC/AC Volt Endurance	:	DC 1000V/AC 750V for 1min
Wiring Pattern at rear end	:	T568A & T568B

Page 1 of 2

Kindly note that any specifications including design, measurements, size, dimension, weight and material specifications mentioned across any technical or commercial document are change by 3C3 India Pvt. Ltd., without any notice.

Copper V-Shaped Angled Patch Panel Shielded Loaded – 1U

Environmental Specifications

Operating Temperature	:	-40°C to +70°C
Storage Temperature	:	-40°C to +70°C
Humidity	:	10% - 90% RH

Standard Compliances/Certifications

- RoHS Certified
- UL Listed
- ASTM B 117 Certified

Ordering Information

Product Code	Description
11330	Copper Panel V Shape Angled Shielded, 24Port Loaded 1U wire manager included