

Customer Outlet Box



The customer outlet Box allows easy and quick installation of cables at the user's site to the various active equipment for FTTx network building.

Features

- Unique design- No screw structure, small size, easy to fix
- High-quality Flame-retardant PC material
- Anti-UV, Ultraviolet resistant and rainfall resistance
- Suitable for splicing
- Support up to 2 drop cables
- Adapter Type SC and LC (Standard), FC(Optional)
- Covered under 3C3® Performance Warranty

Technical Specifications

Material	:	PC
Fiber Capacity Maximum	:	2F
Adapter Types	:	SC/LC
Dimension (H x W x D)	:	105 x 82 x 23mm
Job stress	:	70kpa to 108 kpa
Operating Temperature	:	-5°C ~ +55°C
Insertion Loss	:	≤0.2dB
Mating durability (500 cycles)	:	≤0.2dB

Ordering Information

Product Code	Description
832D2-1000	Customer Outlet Box loaded with Adapter and Pigtail D = Adapter ,1 - SCU Simplex, 2 - SCAPC Simplex, 5 - LCU Simplex, 6 - LCAPC Simplex
83292-0000	FTTH Customer Outlet, Unloaded

Page 1 of 1

Kindly note that any specifications including design, measurements, size, dimension, weight and material specifications mentioned across any technical or commercial document are change by 3C3 India Pvt. Ltd., without any notice.