

DIN Rail Fiber Patch Panel



DIN Rail mount fiber patch panel is designed either to support direct termination or fusion splicing of the fibers. The compact size of the DIN Rail mount patch panel helps to save space especially when it is mounted within enclosures or cabinet with other DIN Rail mount equipment. The patch panel can be loaded with SC adaptors. It can support up to 24 cores.

Features

- Space-Saving installation
- DIN-Rail mountable
- Up to 12 duplex ports
- Covered under 3C3® Performance Warranty

Technical Specifications

Material	: SPCC (Cold rolled steel sheet)
Material thickness	: 1mm
Dimension (WxDxH)	: 155 x 135 x 30mm
Color	: Siemens Grey
Max Connector Capacity	: LC (12LC Duplex) SC (12SC Simplex)
Operating Temperature	: -10°C to +70°C
Pigtails Type	: Single mode
Insertion Loss	: ≤0.3dB
Return Loss	: ≥45dB (UPC)
Repeatability	: ≤0.1dB
Durability	: ≤0.2dB, 1000mattings
Ferrule Material	: Zirconia Ceramic

Ordering Information

Product Code
61CD7-0XXX

Description

DIN Rail Patch Panel, Loaded with Adapters, Pigtails
C = (0 – OS2, 2 – OM2, 3 – OM3, 4 – OM4)
D = (1 - LC simplex, 2 - LC duplex, 3 - SC- Simplex, 4 - SC Duplex)
XXX= Nos of Cores (006 = 6 Core, 012 = 12Core, 024 = 24 Core)