

# FTTA Enclosure Box



The FTTA Pre connectorized factory sealed Plug and play fiber optic enclosure allows easy and quick installation of cables. The fiber splitting and distribution can be done in this box, and it provides solid protection and management for the FTTA network building.

## Features

- Support both wall and Pole mounting
- IP 68 rated
- Accommodate 1x4 PLC and 1x8 PLC ,1x 16 PLC and 1x 24 PLC Splitters
- Industry Standard User interface and made of high impact plastic
- Anti-UV, Ultraviolet resistant and rainfall resistance
- Covered under 3C3® Performance Warranty

## Technical Specifications

Material	:	PC
Fiber Capacity Maximum	:	8F
Adapter Types	:	SC/LC
Job stress	:	70kpa to 108 kpa
Operating Temperature	:	-40°C ~ +80°C
Cable OD	:	6.0mm to 12.0mm
Relative Humidity	:	≤ 95%
Protection	:	IP68
Dimension (L xW xH)	:	225 X 120 X 85mm(4F), 305 X 120 X 85mm(8F), 416 X 120 X 85mm(12F),

## Ordering Information

Product Code	Description
840DE-XXXX	FTTA Enclosure, Loaded C- Adapter ,0=LCU Duplex 1- SCU Duplex E- Core, 0-4F, 1- 8F, 1 – 12F