

Fiber Distribution Box



The Fiber Distribution Box allows easy and quick installation of cables. The fiber splicing, splitting, distribution can be done in this box, and it provides solid protection and management for the FTTx network building.

Features

- Support both wall and Pole mounting
- IP 55 rated
- Accommodation 1 x 4 and 1 x 8 PLC Splitters
- Industry Standard User interface and made of high impact plastic
- Anti-UV, Ultraviolet resistant and rainfall resistance
- Support up to 8 FTTH drops
- Covered under 3C3® Performance Warranty

Technical Specifications

Material	:	PC+ABS
Fiber Capacity Maximum	:	8F
Adapter Types	:	SC/LC
Job stress	:	70kpa to 108 kpa
Operating Temperature	:	-40°C ~ +60°C
Ports	:	2 Inlet 8 outlet ports
Relative Humidity	:	≤ 95%
Protection	:	IP55
Dimension (W xH xD)	:	200 X 215 X 54mm

Ordering Information

Product Code	Description
830DE-1000	Fiber Distribution Box, Loaded
	D = Adapter, 1 - SCU Simplex UPC, 2 - SCAPC Simplex
	E = Core, 1 - 1F, 2 - 2F, 3 - 4F, 4 - 8F

Page 1 of 1

Kindly note that any specifications including design, measurements, size, dimension, weight and material specifications mentioned across any technical or commercial document are change by 3C3 India Pvt. Ltd., without any notice.