

Fiber Optic Enclosure - Flat



Fiber closure is used for connecting and protecting single core or bunch cables. It can be used for aerial- hanger, wall mountable or direct buried applications. 3C3® fiber closures can improve the operation of your network communication system.

Features

- Small Core Horizontal Fiber Optic Splice Closure
- Mechanical seal and sticky cincture seal
- Suitable for straight-through, diverging and connection of FTTH, FTTB all kinds of optical communication passive network
- Body is made up of PP Synthetic Plastics
- Covered under 3C3® Performance Warranty

Constructional Specifications

| | |
|-----------------------------|---|
| Type | : Horizontal |
| Housing Material | : High-intensity Engineering Plastics (ABS) |
| Max. Splice Capacity | : 48F |
| Cable Entry/Exit | : 4 |
| Enclosure Dimension (LxWxH) | : 350 x 145 x 90 mm. |
| Cable diameter range | : Ø10 ~ Ø18.5 mm |
| IP rated | : IP 68 |
| Weight | : 1.3 kg |

Environmental Specifications

| | |
|-----------------------|---------------|
| Operating Temperature | : -40°C~+70°C |
|-----------------------|---------------|

Ordering Information

| Product Code | Description |
|--------------|---|
| 6420E | Enclosure, IP68 Rated, Flat E = Fiber Capacity (1 – 12F, 2 – 24F, 3 – 48F) |