

# Fiber Optic Multi Mode Pigtail



Fiber Optic pigtail is used in permanent connection between patch panels and incoming cables. Pigtails are pre-constructed with connectors. Connector options include LC, SC, FC, ST, MTRJ, and E2000. These are based on 900micron tight buffered cores and suitable for internal use only.

## Features

- Complies to ANSI/TIA-568.3-E, IEC 61300-3-4, IEC 61300-3-6, IEC 60874-1 & ISO/IEC 11801
- LSZH jacket, meets IEC-60332-1 (LSZH) flame rating for standard safety compliant.
- All Assemblies come with Factory test reports
- Bend insensitive fibers
- Available in OM2, OM3 & OM4
- Available in PC, UPC
- Covered under 3C3® Performance Warranty

## Technical Specifications

Type	: Multi-Mode
Insertion Loss	: $\leq 0.3\text{dB}$
Return Loss	: $\geq 35\text{dB}$ (UPC)
Repeatability	: $\leq 0.1\text{dB}$
Durability	: $\leq 0.2\text{dB}$ , 1000mattings
Ferrule Material	: Zirconia Ceramic
Operating Temperature	: $-40^{\circ}\text{C} \sim +85^{\circ}\text{C}$

## Standard Compliances/Certifications

- RoHS Certified

## Ordering Information

Product Code	Description
7BC01-0015	High Link Fiber Optic Multi Mode Pigtail, 1.5M B = (1 - LC, 3 - SC, 5 - ST, 6 - FC) C = Type (2 - OM2, 3 - OM3, 4 - OM4)