

Fiber Optic Single Mode Pigtail



Fiber Optic pigtail is used in permanent connection between patch panels and incoming cables. Pigtails are pre-constructed with connectors. Connector options include LC, SC, FC, ST, MTRJ, and E2000. These are based on 900micron tight buffered cores and suitable for internal use only.

Features

- Complies to ANSI/TIA-568.3-D, ITU-T G.657.A1 (Compatible with G.652.D), IEC 61300-3-4, IEC 61300-3-6, IEC 60874-1, Telcordia GR-326
- LSZH jacket, meets IEC-60332-1 (LSZH) flame rating for standard safety compliant.
- All Assemblies Comes with Factory test reports
- Bend insensitive fibers
- Available in PC, UPC
- Covered under 3C3® Performance Warranty

Technical Specifications

Type	:	Single Mode
Insertion Loss	:	≤0.2dB
Return Loss	:	≥50dB (UPC)
Repeatability	:	≤0.1dB
Durability	:	≤0.2dB, 1000mattings
Ferrule Material	:	Zirconia Ceramic
Operating Temperature	:	-40°C ~ +85°C

Standard Compliances/Certifications

- RoHS Certified

Ordering Information

Product Code

7B001-0015

Description

High Link Fiber Optic Single Mode Pigtail, 1.5M
B = (1 - LC, 3 - SC, 5 - ST, 6 - FC)

Kindly note that any specifications including design, measurements, size, dimension, weight and material specifications mentioned across any technical or commercial document are change by 3C3 India Pvt. Ltd., without any notice.