

# Fiber Optic Patch Panel Wall Mountable 6F ~ 24F



Wall Mount Fiber Optic Patch Panel with lockable systems are recommended for secured high density terminations allowing economical interconnection of fibers for indoor or wall space limitations. Loaded panels come with adapter plates, splice management and Pigtails.

## Features

- Conformance to ANSI/TIA-568.3-D, Telcordia GR-326-CORE, Telcordia GR-1221-CORE, ISO/IEC 11801, IEC 61754 & IEC 61300 series
- Space Saving with its compact & small enclosure design
- Front door design is easy for operation & Fiber's expansion
- Can Manage both splices and terminations
- Can include adapter panels for maximum 24 fiber cores of LC/SC terminations
- Snap-in locker design, easy to change adapter plates for flexible configuration & easy installation
- 8 Nos of  $\varnothing 20$ mm cable entries at top and bottom
- Lockable for added security
- Dimension (H x W x D): (300 x 230 x 100) mm
- Color: Light Grey
- Covered under 3C3® Performance Warranty

# Fiber Optic Patch Panel Wall Mountable 6F/12F/24F

## Technical Specifications

Panel Material	:	SPCC (Cold rolled steel sheet)
Pigtail Types	:	Single Mode                      Multi-Mode
Insertion Loss	:	≤0.2dB                                      ≤0.3dB
Return Loss	:	≥50dB (UPC)                              ≥35dB
Repeatability	:	≤0.1dB
Durability	:	≤0.2dB, 1000mattings
Ferrule Material	:	Zirconia Ceramic
Operating Temperature	:	-25°C ~ +70°C

## Ordering Information

### Product Code

61905-0000

61CD5-0XXX

### Description

Fiber Panel Wall Mount, Single door, Unloaded

Fiber Panel Wall Mount, Single door, Loaded with Adapter Plate, Pigtails and Splice Tray.

C: Type (0- OS2, 1-OM2, 2-OM2, 3-OM3, 4-OM4)

D: Adapter (2 - LC Duplex, 4 - SC Duplex)

XXX = Core (006 - 6core, 012 - 12core, 024 - 24core)