

# Floor Mount Rack



3C3® floor mount racks are multipurpose racks which are scalable and flexible for servers, networking, audio-video, data center and Networking labs applications.

## Features

- Conforms to DIN 41494 and ISO 9001/14001 Standards
- Rack main body is made up of CRCA Steel (1mm -2mm)
- Adjustable 19" equipment mounting angles with U marking provides better mounting flexibility, maximizing the usable mounting space.
- Adjustable depth mounting slots.
- Perforated top cover with left & right cable access cutout with brush.
- Powder coated finish with Seven Tank pre-treatment process.
- Grounding provision is provided.

## Technical Specifications

Rack Standard	: Conforms to DIN 41494 and ISO 9001/14001 Standards
Construction	: Welded
Basic Frame	: Steel four pillars with steel end frame
Front Door	: Honeycomb perforated steel door with 80% perforated area/ Glass Door.
Rear Door	: Honeycomb perforated split door or Plain door.
Intake/Exhaust Fan	: 360 CFM, 230V AC, 50Hz with Wire & Plug and fan tray
Equipment Mounting	: DIN 41494 Standard 10mm. Square slots
Standard Color	: RAL 9004 Black
Top panel	: Removable middle panel & cable access cut-out along with brush.
Standard Rack Mounting	: Heavy duty castor & adjustable feet (Two wheels with break and two wheels without break)
Static Load	: 900 Kg with castor wheel.

*Note: The image shown here is only for reference.*

# Floor Mount Rack

## Accessories Included.

- Fan Modules
- Fixed shelf
- Earthing Kit
- Mounting Hardware
- Power Distribution Unit (PDU)

## Ordering Information

### Product Code

436DE-XXXX

### Description

Floor Mount Rack

D = Dimension of Width \* Depth in mm

0 - 600 \* 800

2 - 600 \* 1200

3 - 800 \* 1000

E = Type of Door

0 - Front Glass + Rear Vented Door

1 - Front Glass + Rear Split Metal Door (Perforated)

2 - Front Perforated + Rear Split Perforated Door

3 - Front Perforated & Rear Single Perforated Door

XX = Accessories

00 - Fans (4 Nos), Fixed Shelf, 2U PDU 6X5/15 Amps Indian Round Pin Socket, 16A MCB, with SPD 230V/50Hz, 1.5 Sq mm\*3 Core, 1.5 Mtr, Cable Length, Mounting Hardware & Earthing kit.

01 - Fans (2 Nos.), PDU 12soc 5/15A (2Nos.) Cantilever Shelf, Hardware Kit.

02 - Fans (4 Nos.), Fixed Shelf, PDU 12soc 5/15A with 16A MCB, Mounting hardware, Horizontal cable manager- 1U (Single Side), earthing kit

03 - Fans(2Nos.), Fixed Shelf, PDU 6x 5/15A With 16A MCB, Mounting hardware, Horizontal Cable manager- 1U (Single side), Earthing kit

04 - Fans (4 Nos.), Vertical PDU 12soc 5/15A Indian Round Pin Socket, 16A MCB & Indicator, 1.5 Sq mm\*3 Core, 3 Mtr Cable Length (2Nos.), Mounting Hardware, Earthing Kit.

XX = Height in U

24 - 24U, 27 - 27U, 32 - 32U, 42 - 42U

**\*Other sizes available upon request.**