

Giga Core™ 1U 144 Fiber Patch Panel



The Fiber Optic Sliding Patch Panel 1U with 4Cutout are innovative, robust and have been designed to accept up to 4 style assemblies. This panel offers a flexible solution to the end user, enabling them to incorporate a multi- functional chassis that allows easy access during installation or rework with no disturbance of the existing cable or fibers. MPO trunk cables connected to 4 individual MPO cassettes with up to 36 fibers in each, loose tube cable to be spliced into standard splice cassettes to allow standard splicing or pre-terminated solutions.

Features

- Standard 19-inch Rack Mountable
- Innovative and robust design
- Unique slide design, structural stability, easy to use and operate, slides smoothly without interference.
- Easy installation: Cassettes can be installed.
- 4 Nos of 20mm diameter at the rear for Cable entries
- Accepts MPO trunk cable.
- Factory pre-terminated and tested modules.
- Covered under 3C3[®] Performance Warranty

Mechanical Specifications

Body Materials : SPCC (cold rolled steel sheet)

Powder Coat Finish : Fine Send Texture
Panel Color : Black RAL 9004
Fiber Mode : OS2, OM3, OM4

Panel Height : 1U

Dimension : 482 x 260 x 44.5 mm

Environmental Specifications

Operation Temperature : $-25^{\circ}\text{C} \sim +55^{\circ}\text{C}$ Storage Temperature : $-20^{\circ}\text{C} \sim +60^{\circ}\text{C}$ Air Pressure : $70\text{kPa} \sim 106\text{kPa}$

Page 1 of 3

Kindly note that any specifications including design, measurements, size, dimension, weight and material specifications mentioned across any technical or commercial document are change by 3C3 India Pvt. Ltd., without any notice.

Document Version: 66075-1000/V3

Date of Revision: 04/2025

Log On to www.3c3.com for recent updates.



Giga Core™ 1U 144 Fiber Patch Panel

MPO - LC Module



Features

- The adapter plate is made of CRCA.
- High performance LC Internal Shutter Adapter adaptors.
- Factory pre-terminated and tested.
- Flexible configuration, fast Installation
- Modular design with higher density, it comes up to 36 LC ports and switches to 3x 12 MPO Connection.
- Quick disassembly, easy installation, no tools required.

Mechanical Specifications

Material : CRCA

Powder Coating Finish : Fine Sand Texture Panel Color : Black RAL 9004

Front Adapter type : 12 Core LC (w/o Flange) × 3Pcs

Front Adapter color : Blue: OS2, Aqua: OM3, Aqua, Magenta: OM4

Rear Adapter Type : 3x MPO Coupler Female

Rear Adapter Color : Black

Dimension (W x D x T) : $106 \times 41 \times 140 \text{mm}$

Page 2 of 3

Kindly note that any specifications including design, measurements, size, dimension, weight and material specifications mentioned across any technical or commercial document are change by 3C3 India Pvt. Ltd., without any notice.



Giga Core™ 1U 144 Fiber Patch Panel

Optical Performances

Specification Value **Insertion Loss** ≤0.2dB Return Loss ≥55dB

Ordering Information

Description Product Code

66075-1000 Giga Core™ Fiber Panel,1U, 4 Cutout, Unloaded 66111-11X3 MPO-LC Module, 3No 12F MPO to 12 Core 66269-9000

Blank Adapter Plate

X = 0 - OS2, 1 - OM3, 2 - OM4 (Aqua), 3 - OM5, 4 - OM4 (Magenta)

Page 3 of 3

Kindly note that any specifications including design, measurements, size, dimension, weight and material specifications mentioned across any technical or commercial document are change by 3C3 India Pvt. Ltd., without any notice.

Document Version: 66075-1000/V3

Date of Revision: 04/2025

Log On to www.3c3.com for recent updates.

Phone: 1800-2020198 | Email: sales@3c3.com | www.3c3.com