

Multi-Mode Fiber Optic Uniboot Patch cords



High-density patch cords are designed with LC connectors in a small-form-factor, paired with 2.0 mm duplex cables. They are ideal for directly connecting switches or network devices within fiber networks, as well as for interconnecting components in structured cabling systems to support high-performance fiber connectivity.

Features

- Conformance to ANSI/TIA-568.3-E, IEC 61300-3-4, IEC 61300-3-6, IEC 60874-1, Telcordia GR-326, ISO/IEC 11801
- True Uniboot (one boot) design
- Bend insensitive fiber
- All Assemblies Comes with Factory test reports
- LSZH jacket, meets IEC-60332 (LSZH) flame rating for standard safety compliant.
- Covered under 3C3® Performance Warranty

Constructional Specifications

Fiber Count	:	2F
Tight Buffer dimension	:	0.60±0.05 mm
Strength Member	:	Aramid Yarn
Outer Sheath	:	LSZH
Sheath Color	:	Aqua
Cable Diameter	:	2.0±0.1mm
Connector Type	:	LCU Uniboot

Optical Specifications

Fiber Type	:	MM, OM4, 50/125µm
Insertion loss	:	≤ 0.3 dB
Return loss	:	≥ 35dB
Durability	:	≤0.2dB (500 Mating)

Multi-Mode Fiber Optic Uniboot Patch cords

Environmental Specifications

Storage Temperature	: -40°C~+70°C
Operating Temperature	: -20°C~+70°C

Regulatory Compliances/Certifications

- ROHS Certified

Ordering Information

Product Code	Description
72422-XXXX	High Density, High Link LCU to LCU, Uniboot Polarity Change, Fiber Optic Patch Cord, Duplex, OM4 XXXX – Length in Decimeter (0010 = 1M, 9990 = 999M)

Kindly note that any specifications including design, measurements, size, dimension, weight and material specifications mentioned across any technical or commercial document are change by 3C3 India Pvt. Ltd., without any notice.