

PIM™ Category 6A U/UTP Patch Cord



High Speed 10 Gigabit PIM™ U/UTP Patch Cable Grey, LSZH, C6A delivers optimal transmission and networking performance with reduced insertion loss and Alien Crosstalk. They are high performance components available in broad range of lengths and designed to meet or exceed all Cat6A specifications. 24 AWG conductors are securely mated with RJ45 plug to deliver superior performance

Features

- Complies to ANSI/TIA-568.2-D and ISO/IEC 11800 Standard
- Quality 24 AWG Stranded flexible cable
- High grade 50µm gold Plated RJ45 connectors
- Improved Strain Relief boot
- Soft latch-cover design for easy depression and anti-snag function.
- 9pin construction
- Use in Cross-connect topology
- 100% assembled and tested in factory.
- Covered by the 3C3® Performance Warranty

Mechanical Specifications

Cable Type	:	Unshielded
Diameter	:	6.3mm
Jacket	:	LSZH
AWG	:	24AWG +26AWG (9th Pin)
Assembly Standard	:	T568A and T568B
Material Plug	:	Transparent thermoplastic material UL 94V-0
Mated	:	≥ 750 RJ45
Application	:	Supports IEEE 802.3, 10G BASE-T, 1000 BASE T, 1000 BASE TX, EIA/TIA-854, ANSI-EIA/TIA-862, ATM, Video, Building Automation Systems and all previous LAN protocols.

PIM™ Category 6A U/UTP Patch Cord

Environmental Specifications

Operating Temperature	: -10°C to +60°C
Storage Temperature	: -40°C to +70°C

Standard Compliances/Certifications

- RoHS Certified

Ordering Information

Product Code	Description
46023-XXXX	PIM™ High Speed 10 Gigabit U/UTP Patch Cord Grey, LSZH, C6A XXXX – Length in Centimeter (3Mtrs and 5Mtrs only)