



3C3<sup>®</sup> Zeta core™ Panel is specially designed to accommodate Zeta Core™ cabling in high end Data Center and Telecommunication central office environment. The shallow depth of Zeta Core™ Panel makes it suitable for low depth copper racking systems or Telecommunication ODFs. The 1U 19″ 144 fiber MPO Panel contains factory controlled and tested Modules can be installed in it. Different types of cassettes are available to deliver optimum Performance and reliability. Integrated fiber management features are provided to secure trunk cables, separate patch cords and maintain safe bend radius during fiber routing.

#### **Features**

- Complies to IEC61754-7, ANSI/TIA-604-5 FOCIS 5, ANSI/TIA 472.AAAD and ISO/IEC 11801
- Patch Panel design rail and easy pullout.
- Easy installation: Cassettes can be installed
- 1U patch panel capacity comes up to 144F fully loaded with 12 modules
- Factory pre-terminated and tested modules are available
- 19" rack mount, the panel is made of cold rolled steel sheet and module is made of plastic

#### **Mechanical Specifications**

Body Materials : SPCC (cold rolled steel sheet)
Painting Finish : Black (fine sand grain spray)

Panel Color : RAL 9004 Black Fiber Mode : OS2, OM3, OM4

Panel Height : 1U

Capacity : 144 LC, 144 Splicing, 72 MPO

Dimension (WxDxH) : 483 mm x 350 mm x 1U

#### **Environmental Specifications**

Page 1 of 4

Kindly note that any specifications including design, measurements, size, dimension, weight and material specifications mentioned across any technical or commercial document are change by 3C3 India Pvt. Ltd., without any notice.

Document Version: 66011-1000/V3

Date of Revision: 04/2025



#### **MPO-LC Module**



#### **Features**

- The module is made of plastic.
- Module capacity comes up to 12F fully loaded
- Factory pre-terminated and tested.
- High performance zirconia sleeve adaptors.
- Modular design with higher density, it comes up to 12 LC ports and switches to MPO connection

### Configuration

Material : Plastic Color : Black

(front)Adapter type : 3x LC Quad (front)Adapter color : Aqua: OM3/OM4

Blue: SM-UPC; Green: SM-APC

(rear)Adapter type : MPO (rear)Adapter color : Black

Connector A : LC-UPC, 0.9mm LC-APC, 0.9mm

LC-APC, 0.9mn

Connector B : MPO-APC MPO-PC

IVIFU-FC

Polarity : Type B

Dimension (W x D x H)  $\qquad \qquad : \quad 90 \text{ x } 130 \text{ x } 11.7 \text{mm}$ 

#### **Optical Specifications**

 Type
 I.L Max
 R. L

 MPO (SM APC)
 : ≤0.70dB
 ≥50dB

 MPO (MM PC)
 : ≤0.6dB
 ≥25dB

 LC (SM PC)
 : ≤0.30dB
 ≥50dB

 LC (MM PC)
 : ≤0.30dB
 ≥35dB

Page 2 of 4

Kindly note that any specifications including design, measurements, size, dimension, weight and material specifications mentioned across any technical or commercial document are change by 3C3 India Pvt. Ltd., without any notice.

Document Version: 66011-1000/V3

Date of Revision: 04/2025



#### **MPO-MPO Module**



#### **Features**

- The module is made of plastic.
- Factory pre-terminated and tested.
- High performance zirconia sleeve adaptors.
- Modular design with higher density, it comes up to 3 MPO Duplex adapter ports which switch to MPO connectivity

### **Technical Specifications**

Material : Plastic
Color : Black
(front)Adapter type : MPO
(front)Adapter color : Black
(rear)Adapter type : MPO
(rear)Adapter color : Black

Connector A : MPO - APC 12F

MPO - PC 12F

Connector B : MPO- APC 12F

MPO - PC 12F

Polarity : Type B

Dimension (W x D x H)  $= 90 \times 130 \times 11.7 \text{mm}$ 

### **Optical Specifications**

TypeI.L MaxR. LMPO (SM APC):  $\leq 0.70 dB$  $\geq 50 dB$ MPO (MM PC):  $\leq 0.6 dB$  $\geq 25 dB$ 

Page 3 of 4

Kindly note that any specifications including design, measurements, size, dimension, weight and material specifications mentioned across any technical or commercial document are change by 3C3 India Pvt. Ltd., without any notice.

Document Version: 66011-1000/V3

Date of Revision: 04/2025



## **Splicing Module - LC**



#### **Features**

- The module is made of Plastic
- Factory Pre terminated and Tested
- High Performance zirconia sleeve adaptors
- 12 Colored Pigtails

### **Technical Specifications**

Material : Plastic
Color : Black
(front)Adapter type : 3LC Quad
(front)Adapter color : Blue/Aqua

Dimension (W x D x H)  $= 90 \times 130 \times 11.7 \text{mm}$ 

## **Optical Performances**

Type I.L Max R. L LC (SM PC) :  $\leq 0.30$ dB  $\geq 50$ dB LC (MM PC) :  $\leq 0.30$ dB  $\geq 35$ dB

#### **Ordering Information**

Product Code	Description
66011-1000	Zeta Core™ Fiber Panel 144F 1U Unloaded
66100-05X0	MPO-LC Module, 1No 12F MPO to 3LC Quad
66106-06X0	MPO- MPO Coupler Cassette, 1No 6F MPO to 6F MPO
66103-05X0	Splicing Module-LC, Colored Pigtails, 12F LC Splice Cassette to 3x LC Quad
	X=Type, 0- OS2, 1-OM3, 2-OM4 (Aqua), 3-OM5, 4- OM4 (Magenta)

Page 4 of 4

Kindly note that any specifications including design, measurements, size, dimension, weight and material specifications mentioned across any technical or commercial document are change by 3C3 India Pvt. Ltd., without any notice.

Document Version: 66011-1000/V3

Date of Revision: 04/2025